



NextGen Curemate 550 – Climatic Cabinet for Curing 550L

Standards: [ASTM C109](#), [ASTM C511](#), [EN 196-8](#), [EN 196-1](#), [EN ISO 679](#)



ULTIMATE USER-FRIENDLINESS



LEADING DEPENDABILITY AND RELIABILITY



STRICT COMPLIANCE WITH INDUSTRY STANDARDS



STOCKED CONSUMABLES AND SPARES



TRUSTED AFTER SALES TECHNICAL SUPPORT



LIFETIME PRODUCT SUPPORT ADVANTAGE

Description

NG-CureMate 750 - Climatic Curing Chamber has a Capacity 550 Litre. Digital control unit (0.1 resolution). Temperature (e.g. 20.0°C) and relative humidity (e.g. 95.0% RH) are displayed at all times as well as all the other phases (cooling, heating, ventilation, humidification, etc.).

Features

- Temperature range: from +10°C to +40°C (± 1°C).
- Humidity range: from 80% to 100% (saturation).
- Humidifier: automatically-generated humidity by vaporization.
- Inner/outer structure: Entirely in AISI 304 stainless steel. Grid shelves.
- The cabinet top can be used as a work bench.
- Thermal insulation: in 60 mm thick self-extinguishing polyurethane (CFC-free) foam.
- Doors: mounted on special hinges for automatic closure. Four doors and eight (plasticized steel) shelves, supplied as standard.



GET A QUOTE



- Up to six extra shelves can be added.
- Refrigerating system: airtight type with air condensation and R 404a ecological (CFC-free) gas.
- Heating: thermostatically-controlled heating element with low thermal inertia.

Parameters

- Power supply: 220 V, 50 Hz, single phase, 1600 W
- Dimensions: 2260 x 700 x 850 (h) mm
- Weight: 205 kg

[GET A QUOTE](#)