



## Classic Analogue Shore Durometer with Test Stand Options

**Standards:** DIN ISO 7619, DIN EN ISO 868, ASTM D 2240, BS 903 Part. A 26, NF T 51-174



German  
Manufactured



Highest  
Accuracy and  
Repeatability



Industry  
Certified



Complete  
Calibration  
Solution



Free Proof of  
Concept



Custom  
Turnkey  
Solution  
Availability



**Video:** [https://youtu.be/SM\\_XIXniR2o](https://youtu.be/SM_XIXniR2o)

### Description:

This Germany manufactured system has been the global landmark of Shore hardness testing systems since 1954. With ever enhanced ergonomic design, the HP Shore Hardness Tester is both visually appealing and precise rubber and plastic testing system as it has been for nearly 50 years. The HP system is world renowned best seller hardness tester with over 100,000 units sold to satisfied clients globally. It is considered the world's highest and most used portable shore hardness tester.

The system is designed to provide a combination of light weight and extraordinary durability for a compact shore testing machine. The systems are carefully assembled, quality control tested and certified by the German manufacturer, Bareiss. The system is designed so that the friction caused by travelling is avoided by the use of various size bearing balls which contribute to a perfect smooth travel for the indenter. This German manufactured system has the versatility of testing various Shore and non-Shore scales. Additionally, it can be combined with a manual or an automatic test stand options for an even more precise and repeatable testing results.

### Test Methods:

Shore A, A0/E, B, 0, C, D, D0, 00, 000, Bareiss Variant C (Asker C)

### Features and Benefits:

- ✓ *Aluminum Chassis* – Shore system is suitable for field work due to its light weight and durable chassis.
- ✓ *Use of Ball Bearings* - Reduces friction during the travel of indenter to achieve the best measuring results.
- ✓ *High Accuracy* - Achieves 0.5 unit of Shore compared with the allowable tolerance 1.0 unit of Shore outlined in the industry standards.
- ✓ *Wide Model Range* - Available in different Shore and non-Shore scales.



### Models:

Scale	Load	Spring Force	Foot Size	Indenter Travel	Min Sample Thickness	Indenter Shape
A	1 Kg	8.050 N	18 mm	2.5 mm	4 mm (DIN EN ISO 868) 6 mm (all other standards)	35°
D	5 Kg	44.45 N	18 mm	2.5 mm	4 mm (DIN EN ISO 868) 6 mm (all other standards)	30°
0	1 Kg	8.050 N	>500mm <sup>2</sup>	2.5 mm	6 mm (all standards)	Ø3/32"
B	1 Kg	8.050 N	18 mm	2.5 mm	6 mm (all standards)	30°
C	5 Kg	44.45 N	18 mm	2.5 mm	6 mm (all standards)	35°
D0	5 Kg	44.45 N	>500mm <sup>2</sup>	2.5 mm	6 mm (all standards)	Ø3/32"
A0	1 Kg	8.050 N	>500mm <sup>2</sup>	2.5 mm	6 mm (all standards)	Ø5mm
E	1 Kg	8.050 N	>500mm <sup>2</sup>	2.5 mm	6 mm (all standards)	Ø5mm
00	400 g	1.111 N	>500mm <sup>2</sup>	2.5 mm	6 mm (all standards)	Ø3/32"
000	400 g	1.111 N	>500mm <sup>2</sup>	2.5 mm	6 mm (all standards)	r=6.35mm
000S	400 g	1.932 N	>500mm <sup>2</sup>	5.0 mm	6 mm (all standards)	r=10.70mm

**NORTH AMERICA (CORPORATE HEADQUARTERS):** 170-422 Richards St., Vancouver, BC, V6B 2Z4 Canada

**CALIFORNIA:** 3503 Jack Northrop Ave., Suite # AF937, Hawthorne, CA 90250

**Toll Free: +1 (888) 332-3582 | Fax: +1 905 247-0555 | [www.nextgentest.com](http://www.nextgentest.com)**



### Calibration:

As a national accredited DAkkS/DKD laboratory, our partners are officially authorized to perform repair and recalibration services on all types of hardness testers in accordance with specified standards and to issue the DAkkS/DKD certificate.



### Loaner Program for Testing Heads:


Avoid service interruptions by getting a tester head on loan. Contact us today to ask how.

### Sample Preparation Service:

We welcome you to send your specimens to our facility to confirm that our equipment's accuracy is perfectly in line with your expectations. Contact us today to learn more.

### Training:

We stand behind our product. Should you require additional training support, please contact us and we would be happy to assist your most suitable remote communication method.



65 mm

28 mm

Weight : 250 g



**NORTH AMERICA (CORPORATE HEADQUARTERS):** 170-422 Richards St., Vancouver, BC, V6B 2Z4 Canada

**CALIFORNIA:** 3503 Jack Northrop Ave., Suite # AF937, Hawthorne, CA 90250

**Toll Free:** +1 (888) 332-3582 | **Fax:** +1 905 247-0555 | [www.nextgentest.com](http://www.nextgentest.com)



## Accessories:

### NG-BS 61 II test stand:

This Automatic test stand is perfectly compatible with our HP units allowing for hardness measurements in accordance with Shore standards. The pick-up device found on the test stand allows for quick and easy clamping of the hardness tester. Manual test stand option is also available.



### Calibration device for HP and HPE II:

In compliance with ISO 9000 the operator should perform a periodical equipment calibration. With this calibration device the accuracy of the Shore hardness tester is controlled. It allows for a quick control of the spring force in increments of ten for the measuring ranges including Shore A/B/0/C/D/DO and L, L/c.



DIN 53 505, EN ISO 868, NF EN ISO 868, ASTM D2240, JIS K 6253.



### Reference plates

Standard rubber blocks are used to ensure the metrological capability of the measuring device according to the Shore standard during the frequency of recalibration. The rubber blocks are embedded in a holder made of stainless steel.

The calibration stands can come with single, 3, 5 or 6 plates including DAkkS/DKD calibration certificate

### DAkkS/DKD calibration certificate

The purpose of the hardness tester calibration is to determine the unit's measure output against the standard reference. Once the unit is confirmed to meet the testing criteria, a calibration certificate is then issued indicating the measuring results and the corresponding measurement uncertainties and the instrument is marked as calibrated.

All supplied corresponding documentation offered with the calibration certificate provides traceability in accordance to national standards.

### Control of the measuring distance with DAkkS/DKD / WKS Certificate

- ✓ 20 Shore
- ✓ 40 Shore
- ✓ 60 Shore
- ✓ 80 Shore





**NEXTGEN**  
**MATERIAL TESTING**

YOUR QUALITY TESTING CHOICE



\* Request a [formal quotation](#) or send an e-mail to [sales@nextgentest.com](mailto:sales@nextgentest.com) for the most up-to-date pricing and applicable discounts and incentives

---

**NORTH AMERICA (CORPORATE HEADQUARTERS):** 170-422 Richards St., Vancouver, BC, V6B 2Z4 Canada

**CALIFORNIA:** 3503 Jack Northrop Ave., Suite # AF937, Hawthorne, CA 90250

**Toll Free:** +1 (888) 332-3582 | **Fax:** +1 905 247-0555 | [www.nextgentest.com](http://www.nextgentest.com)