

GenGrind SA-I 250S 10" Single Wheel Semi Automatic Grinder & Polisher – Variable Speed 100-1000rpm – Individual Force Control – Touch Screen Controlled with Automatic Specimen Mover Power Head – (various wheel sizes available)





Description

Discover the GenGrind SA-I 250S, your ultimate answer to grinding

and polishing needs. Equipped with a spacious 10"Ø wheel

(254mmØ), it offers automatic two-direction control and stepless variable speed. Its intuitive touch screen, enriched by advanced programming and parameter storage, ensures user-friendly operation.

Experience unmatched efficiency through the powerful individual-pressure head, featuring adjustable speed, clockwise rotation, and pressure. Elevate your sample preparation effortlessly with the GenGrind SA-I 250S.

GenGrind SA-I 250S Features

- Remarkable cost-effectiveness, offering stable quality and versatile functions, easily customizable to cater to various customer requirements.
- Crafted from a single piece of aluminum alloy, the machine base guarantees lightweight construction, exceptional shock absorption, and corrosion resistance.
- Enjoy a single working plate with standard dimensions of 10" diameter (254mm)
- Efficiently polish 6 samples of 30mm diameter in a single operation (various other sizes available upon request).
- The sleek ABS shell exudes a sophisticated appearance, adding a touch of elegance to the machine's design.
- Experience automatic cleaning facilitated by the built-in nozzle with a waste collection tank.
- Intuitive touch screen display control ensures clear interface and a user friendly simple operation.
- Set parameters for testing time, rotation speed, and pressure, tailoring the machine to your needs.
- Opt for the optional electromagnetic clutch for the grinding head, allowing convenient and swift operation.
- Choose between stepless speed regulation (100-1000r/min) or four constant speed options, with room for defining three common speeds for different stages of preparation.

NORTH AMERICA (CORPORATE HEADQUARTERS): 170-422 Richards St., Vancouver, BC, V6B 2Z4 Canada CALIFORNIA: 3503 Jack Northrop Ave., Suite # AF937, Hawthorne, CA 90250



- Store up to 100 sets of grinding and polishing programs, enabling quick program recall.
- Embrace the magnetic disc design for swift disc changes, enhancing efficiency during sandpaper and polishing cloth replacement.
- Seamlessly handle samples with the free-rotating sample chuck design, complemented by an internal lighting system for easy sample placement.
- Benefit from the machine's three-phase silent motor and stepping motor combination, ensuring stable rotation, minimal noise, and extended lifespan.

GenGrind SA-I 250S Standard Configuration

- GenGrind SA-I 250S Single Wheel Semi Automatic Grinder and Polisher with Individual
 Pneumatic Force Control
- Grinding Plate 254mm
- Polishing Cloth with PSA (250mm) (4)
- Grinding Papers 400# (4)
- Grinding Papers 800# (4)
- Grinding Paper 1200# (4)
- Waterproofing Ring (On Machine)
- Paper Disc
- Magnetic Disc
- Water Inlet Hose 0.75"
- Water Outlet Hose 32mm
- Power Line and Operational Manual

GenGrind SA-I 250S Technical Specifications

Model	GenGrind SA-I 250S
Disc Diameter	254mm (10") with Magnetic Disc
Speed of Working Plate	100-1000rpm Stepless Speed Supports Clockwise and Counter clockwise directions
Four Level Constant Speeds	V1=300rpm, V2=500rpm, V3=800rpm, V4=1000rpm (each speed can be set between 100-1400rpm)
Grinding Head Speed	0-120rpm
Sample Holder	Standard is 6pcs @ 30mm Dia. (other sizes available upon request - Φ25mm, Φ30mm, Φ40mm or 1", 1.25", 1.5" or custom)
Automatic Mode	Can program speed, running time, grinding wheel direction and timing functions
Sample Pressure Range	0-0.5MPa (Commonly 0.2-0.3MPa)
Pressure Loading Type	Single Point Pneumatic Pressure
Timing Function	0-99 minutes

NORTH AMERICA (CORPORATE HEADQUARTERS): 170-422 Richards St., Vancouver, BC, V6B 2Z4 Canada CALIFORNIA: 3503 Jack Northrop Ave., Suite # AF937, Hawthorne, CA 90250





YOUR QUALITY TESTING CHOICE

Grinding Head Lock Mode	Manual Lock (Automatic Electronic Optional)
Grinding Head Power	0.2kW (Clockwise Rotation)
Working Wheel Power	1.1kW (Clockwise and Counter Clockwise)
Power Supply	110v 50/60Hz 1.8kW
Dimensions & Weight	19.7" x 30.3" x 27.6" / 500 x 770 x 700 mm 176lbs / 80kg

Note: Check out our <u>consumables catalogue</u> starting on Page 3 for Mounting Press consumables!

* Request a <u>formal quotation</u> or send an e-mail to <u>sales@nextgentest.com</u> for the most up-to-date pricing and applicable discounts and incentives

NORTH AMERICA (CORPORATE HEADQUARTERS): 170-422 Richards St., Vancouver, BC, V6B 2Z4 Canada CALIFORNIA: 3503 Jack Northrop Ave., Suite # AF937, Hawthorne, CA 90250 Toll Free:+1 (888) 332-3582 | Fax: +1 905 247-0555 | www.nextgentest.com